

Safety data sheet
According to 1907/2006/EC, Article 31 REACH

Printing date 22.04.2016

Version: 5

Revision: 22.04.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **POWERHOUSE NEW (Listed NSF A8: n° 152106)**

Article number: 02820001

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC35 Washing and cleaning products (including solvent based products)

Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Cleaning material/ Detergent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

ZEP UK Ltd

PO Box 12 Tanhouse Lane

Widnes Cheshire, WA8 0RR

United Kingdom

Phone: +44 (0)151 422 1000

FAX: +44 (0)151 422 1011

@: info@zep.co.uk

web: www.zep.co.uk

ZEP Industries BV

Vierlinghweg 30

4612 PN Bergen op Zoom

The Netherlands

Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117

Fax:(NL) + 31 164 266 710 (B) + 32 2 347 1395

@: sales@zepenelux.com

ZEP ITALIA SRL

Via Netunese Km. 25.000

04011 Aprilia (LT) - Italy

Tel: +39.06.926691

Fax: +39.06.92747061

@: tecnico@zepeurope.com

Sito: www.zep.it

Further information obtainable from:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

1.4 Emergency telephone number:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 22.04.2016

Version: 5

Revision: 22.04.2016

Trade name: **POWERHOUSE NEW** (Listed NSF A8: n° 152106)

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS05

· Signal word *Danger*

· Hazard-determining components of labelling:

2-aminoethanol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1, H220 Press. Gas C, H280	2.5-5%
CAS: 141-43-5 EINECS: 205-483-3 Reg.nr.: 01-2119486455-28-xxxx	2-aminoethanol ⚠ Skin Corr. 1B, H314 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	2.5-5%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 012119486944-21-xxxx	propane ⚠ Flam. Gas 1, H220 Press. Gas C, H280	2.5-5%
CAS: 7320-34-5 EINECS: 230-785-7	tetrapotassium pyrophosphate ⚠ Eye Irrit. 2, H319	1-2.5%

· Ingredients according to Detergents Regulation 648/2004/EC

For the wording of the listed hazard phrases refer to section 16.

ISOPROPYL ALCOHOL	15 - 30%
Aliphatic hydrocarbons	5 - 15%
Phosphates, Nonionic surfactants	< 5%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation: In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

(Contd. on page 3)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 22.04.2016

Version: 5

Revision: 22.04.2016

Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)

(Contd. of page 2)

- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
 Drink plenty of water and provide fresh air. Call for a doctor immediately.
 Seek immediate medical advice.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 Use neutralising agent.
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
- **6.4 Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 Keep away from heat and direct sunlight.
 Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
 Do not spray onto a naked flame or any incandescent material.
 Keep ignition sources away - Do not smoke.
 Keep respiratory protective device available.
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

67-63-0 propan-2-ol (10-25%)

WEL (Great Britain)

Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

(Contd. on page 4)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 22.04.2016

Version: 5

Revision: 22.04.2016

Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)

(Contd. of page 3)

34590-94-8 (2-methoxymethylethoxy)propanol (2.5-5%)

WEL (Great Britain)	Long-term value: 308 mg/m ³ , 50 ppm Sk
IOELV (European Union)	Long-term value: 308 mg/m ³ , 50 ppm Skin

106-97-8 butane (2.5-5%)

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
---------------------	---

141-43-5 2-aminoethanol (2.5-5%)

WEL (Great Britain)	Short-term value: 7.6 mg/m ³ , 3 ppm Long-term value: 2.5 mg/m ³ , 1 ppm Sk
IOELV (European Union)	Short-term value: 7.6 mg/m ³ , 3 ppm Long-term value: 2.5 mg/m ³ , 1 ppm Skin

· DNELs
67-63-0 propan-2-ol

Oral	DNEL Long term-systemic	26 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	319 mg/kg human/day (consumer) 888 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m ³	89 mg/m ³ (consumer) 500 mg/m ³ (worker)

· PNECs
67-63-0 propan-2-ol

PNEC Freshwater mg/L	140.9 mg/L (-)
PNEC Marinewater mg/L	140.9 mg/L (-)
PNEC Freshwater sediment	552 mg/Kg (-)
PNEC Marine water sediment	552 mg/Kg (-)
PNEC Intermittent release	140.9 mg/L (-)
PNEC Soil	28 mg/Kg (-)

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

· **Protection of hands:**



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· **Not suitable are gloves made of the following materials:** Strong material gloves

(Contd. on page 5)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 22.04.2016

Version: 5

Revision: 22.04.2016

Trade name: **POWERHOUSE NEW** (Listed NSF A8: n° 152106)

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Aerosol
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.

· pH-value at 20 °C: 11.5

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	82 °C

· Flash point: < 0 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 425 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:	2.0 Vol %
Upper:	12.0 Vol %

· Vapour pressure at 20 °C: 42 hPa

· Density at 20 °C: 0.95 g/cm³

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with water:

Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Organic solvents:	24.5 %
EU-VOC:	261.2 g/l
EU-VOC	27.50 %
Swiss VOC:	27.50 %

Solids content: 1.0 %

· 9.2 Other information: No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity: No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions: No dangerous reactions known.

(Contd. on page 6)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 22.04.2016

Version: 5

Revision: 22.04.2016

Trade name: **POWERHOUSE NEW (Listed NSF A8: n° 152106)**

(Contd. of page 5)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

67-63-0 propan-2-ol

Oral	LD50	>5000 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (rab)
Inhalative	LC50 / 4 h	30 mg/ltr (Rat)
	LC50 / 96 h	9640 mg/ltr (fish)
	EC50 / 24 h	>1000 mg/ltr (Daphnia magna (water flea))

106-97-8 butane

Inhalative	LC50 / 4 h	658 mg/ltr (Rat)
------------	------------	------------------

141-43-5 2-aminoethanol

Oral	LD50	1720 mg/kg (Rat)
Dermal	LD50	1018 mg/kg (Rabbit)
	LC50 / 48 h	> 200 mg/ltr (<i>Lepomus gobbosus</i> (Zonnebaars))
	EC 50 / 48 h	> 100 mg/ltr (<i>Daphnia magna</i> (water flea))

7320-34-5 tetrapotassium pyrophosphate

Oral	LD50	>2000 mg/kg (Mouse)
		>2000 mg/kg (Rat)
		>7940 mg/kg (Rabbit)
	LC50 / 48 h	>100 mg/ltr (<i>Daphnia magna</i> (water flea))
	LC50 / 96 h	>100 mg/ltr (<i>Oncorhynchus mykiss</i> (Rainbow trout))

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 7)

Safety data sheet
According to 1907/2006/EC, Article 31 REACH

Printing date 22.04.2016

Version: 5

Revision: 22.04.2016

Trade name: **POWERHOUSE NEW (Listed NSF A8: n° 152106)**

(Contd. of page 6)

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number
- ADR, IMDG, IATA

UN1950

- 14.2 UN proper shipping name

- ADR
- IMDG
- IATA

1950 AEROSOLS

AEROSOLS

Aerosols, flammable

- 14.3 Transport hazard class(es)

- ADR



- Class
- Label

2 5F Gases.

2.1

- IMDG, IATA



- Class
- Label

2.1

2.1

- 14.4 Packing group

- ADR, IMDG, IATA

Void

- 14.5 Environmental hazards:

- Marine pollutant:

No

- 14.6 Special precautions for user

- Danger code (Kemler):

- EMS Number:

- Stowage Code

Warning: Gases.

-

F-D,S-U

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:

Category A. For AEROSOLS with a capacity above 1 litre:

Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except

for division 1.4. For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2. For

WASTE AEROSOLS: Segregation as for the appropriate

subdivision of class 2.

- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

- Transport/Additional information:

- ADR

- Limited quantities (LQ)

1L

(Contd. on page 8)

GB

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 22.04.2016

Version: 5

Revision: 22.04.2016

Trade name: **POWERHOUSE NEW (Listed NSF A8: n° 152106)**

(Contd. of page 7)

· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
<hr style="border-top: 1px dashed black;"/>	
· IMDG	IL
· Limited quantities (LQ)	Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Reg. (EC) n. 1272/2008 - CLP;
 Reg. (EC) n. 1907/2006 – Reach;
 Reg. (EC) n. 2015/830 annex II of REACH;
 Reg. (EC) n. 648/04 (Detergents);
 Reg. (EC) n. 528/12 (Biocides BPR);
 Reg. (EC) n. 1223/2009 (Cosmetics);
 Dir. 06/08 ADR – RID - IMDG - IATA;
 Dir. 47/08 (Aerosols); Dir. 12/18 (Seveso III);
 Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	25-50

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.
 H225 Highly flammable liquid and vapour.
 H280 Contains gas under pressure; may explode if heated.
 H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H336 May cause drowsiness or dizziness.

· **Department issuing SDS:**

Customer Service
 NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710
 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395
 IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61
 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· **Contact:**

(Contd. on page 9)

Safety data sheet
According to 1907/2006/EC, Article 31 REACH

Printing date 22.04.2016

Version: 5

Revision: 22.04.2016

Trade name: POWERHOUSE NEW (Listed NSF A8: n° 152106)

(Contd. of page 8)

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases, Hazard Category 1

Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

* **Data compared to the previous version altered.**