

Safety data sheet
According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 7

Revision: 30.05.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **CHOKE & CARBURATOR CLEANER NEW**

Article number: 02860001

1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC35 Washing and cleaning products (including solvent based products)

Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Application of the substance / the mixture

Solvents

Cleaning material/ Detergent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

ZEP UK Ltd
Tanhouse Lane
Widnes Cheshire, WA8 0RR
United Kingdom
Tel: +44 (0)151 422 1000
Fax: +44 (0)151 422 1011
@: info@zep.co.uk
web: www.zep.co.uk

ZEP Industries BV
Vierlinghweg 30
4612 PN Bergen op Zoom
The Netherlands
Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117
Fax: (NL) + 31 164 266 710 (B) + 32 2 347 1395
@: sales@zepbenelux.com

ZEP ITALIA SRL
Via Netunese Km. 25.000
04011 Aprilia (LT) - Italy
Tel: +39.06.926691
Fax: +39.06.92747061
@: tecnico@zpeurope.com
Sito: www.zep.it

Further information obtainable from:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

1.4 Emergency telephone number:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

(Contd. on page 2)

-GB

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 7

Revision: 30.05.2017

Trade name: **CHOKE & CARBURATOR CLEANER NEW**

(Contd. of page 1)

STOT SE 3 H336 May cause drowsiness or dizziness.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02

GHS07

Signal word Danger**Hazard-determining components of labelling:**

Naphtha (petroleum), hydrotreated light
 butanone
 propan-2-ol

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container. May burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P251 Do not pierce or burn, even after use.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.**Results of PBT and vPvB assessment**

PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene (mix) ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-50%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 012119486944-21-xxxx	propane ⚠ Flam. Gas 1, H220 Press. Gas C, H280	10-25%
CAS: 64742-49-0 EINECS: 265-151-9 Reg.nr.: 01-2119473851-33-xxxx	Naphtha (petroleum), hydrotreated light ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	10-25%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	5-10%

(Contd. on page 3)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 7

Revision: 30.05.2017

Trade name: CHOKE & CARBURATOR CLEANER NEW


(Contd. of page 2)

CAS: 111-76-2

EINECS: 203-905-0

Reg.nr.: 01-2119475108-36-XXXX

2-butoxyethanol

 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319

1-2.5%

 · **Ingredients according to Detergents Regulation 648/2004/EC** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Seek immediate medical advice.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Protect from heat and direct sunlight.

(Contd. on page 4)

GB

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 7

Revision: 30.05.2017

Trade name: **CHOKE & CARBURATOR CLEANER NEW**

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:****1330-20-7 xylene (mix) (25-50%)**

WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
---------------------	--

IOELV (European Union)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
------------------------	--

78-93-3 butanone (10-25%)

WEL (Great Britain)	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
---------------------	---

IOELV (European Union)	Short-term value: 900 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm
------------------------	---

67-63-0 propan-2-ol (5-10%)

WEL (Great Britain)	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
---------------------	--

111-76-2 2-butoxyethanol (1-2.5%)

WEL (Great Britain)	Short-term value: 246 mg/m ³ , 50 ppm Long-term value: 123 mg/m ³ , 25 ppm Sk, BMGV
---------------------	---

IOELV (European Union)	Short-term value: 246 mg/m ³ , 50 ppm Long-term value: 98 mg/m ³ , 20 ppm Skin
------------------------	--

· **DNELs****78-93-3 butanone**

Oral	DNEL acute-systemic	31 mg/kg human/day (worker)
Dermal	DNEL Acute-systemic	412 mg/kg human/day (worker)
Inhalative	DNEL Acute-systemic mg/m ³	106 mg/m ³ (worker)

67-63-0 propan-2-ol

Oral	DNEL Long term-systemic	26 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	319 mg/kg human/day (consumer)
		888 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m ³	89 mg/m ³ (consumer)
		500 mg/m ³ (worker)

· **PNECs****67-63-0 propan-2-ol**

PNEC Freshwater mg/L	140.9 mg/L
PNEC Marinewater mg/L	140.9 mg/L
PNEC Freshwater sediment	552 mg/Kg
PNEC Marine water sediment	552 mg/Kg
PNEC Intermittent release	140.9 mg/L
PNEC Soil	28 mg/Kg

· **Ingredients with biological limit values:****1330-20-7 xylene (mix) (25-50%)**

BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
----------------------	--

(Contd. on page 5)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 7

Revision: 30.05.2017

Trade name: **CHOKE & CARBURATOR CLEANER NEW**

(Contd. of page 4)

78-93-3 butanone (10-25%)

BMGV (Great Britain) 70 µmol/L
 Medium: urine
 Sampling time: post shift
 Parameter: butan-2-one

111-76-2 2-butoxyethanol (1-2.5%)

BMGV (Great Britain) 240 mmol/mol creatinine
 Medium: urine
 Sampling time: post shift
 Parameter: butoxyacetic acid

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.
 Avoid contact with the eyes and skin.

· **Respiratory protection:**

Filter B
 Filter AX

· **Protection of hands:**

Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
 The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· **Not suitable are gloves made of the following materials:** Strong material gloves

· **Eye protection:**

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form: Aerosol
Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: -44 °C

· **Flash point:** < 0 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 425 °C

(Contd. on page 6)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 7

Revision: 30.05.2017

Trade name: **CHOKE & CARBURATOR CLEANER NEW**

(Contd. of page 5)

· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	12.0 Vol %
· Vapour pressure at 20 °C:	3500 hPa
· Density at 20 °C:	0.745 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Insoluble.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	99.9 %
Swiss VOC:	100.00 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

1330-20-7 xylene (mix)

Oral	LD50	4300 mg/kg (Rat)
Dermal	LD50	2000 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	6350 mg/ltr (Rat)
	LC50 / 96 h	3.77-13.5 mg/ltr (fish)
	EC 50 / 48 h	7.4 mg/ltr (Daphnia magna (water flea))

78-93-3 butanone

Oral	LD50	2737 mg/kg (Rat)
Dermal	LD50	5000 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	20 mg/ltr (Rat)
	EC50	>100 mg/ltr (Selenastrum capricornutum (Algae))
	EC 50 / 48 h	>5000 mg/ltr (Daphnia magna (water flea))
	EC 50 / 96 h	>2500 mg/ltr (Pimephales promelas)

64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	>2000 mg/kg (Rat)
------	------	-------------------

(Contd. on page 7)

GB

Safety data sheet
According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 7

Revision: 30.05.2017

Trade name: **CHOKE & CARBURATOR CLEANER NEW**

(Contd. of page 6)

Dermal	LD50	>2000 mg/kg (Rat)
Inhalative	LC50 / 4 h	>20 mg/ltr (Rat)
	LC50	10-100 mg/l (Selenastrum capricornutum (Algae)) 1-10 mg/l (fish)
67-63-0 propan-2-ol		
Oral	LD50	>5000 mg/kg (Rat)
Dermal	LD50	6290 mg/kg (rab)
Inhalative	LC50 / 4 h	30 mg/ltr (Rat)
	LC50 / 8 h	12000-19000 mg/m3 (Rat)
	LC50 / 96 h	9640 mg/ltr (fish) >1400 mg/ltr (Lepomus gobbosus (Zonnebaars)) 6550 mg/ltr (Pimephales promelas)
	EC50 / 24 h	>1000 mg/ltr (Daphnia magna (water flea))
	EC 50 / 48 h	10000 mg/ltr (Pimephales promelas)
111-76-2 2-butoxyethanol		
Oral	LD50	470 mg/kg (Rat) 320 mg/kg (Rabbit)
Dermal	LD50	400-500 mg/kg (rab) 2270 mg/kg (Rat)
Inhalative	LC50 / 4 h	2.21 mg/ltr (Rat)
	LC50 / 48 h	1815 mg/ltr (Daphnia magna (water flea))
	LC50 / 96 h	1490 mg/ltr (Lepomis Macrochirus (Bluegill Sunfish))

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 8)

Safety data sheet
According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 7

Revision: 30.05.2017



Trade name: **CHOKE & CARBURATOR CLEANER NEW**

(Contd. of page 7)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Disposal must be made according to official regulations
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|--|
| · 14.1 UN-Number | |
| · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name | |
| · ADR | 1950 AEROSOLS |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 2 5F Gases. |
| · Label | 2.1 |
| · IMDG, IATA | |
|  | |
| · Class | 2.1 |
| · Label | 2.1 |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Warning: Gases. |
| · Danger code (Kemler): | - |
| · EMS Number: | F-D,S-U |
| · Stowage Code | SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. |
| · Segregation Code | SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0
Not permitted as Excepted Quantity |
| · Transport category | 2 |

(Contd. on page 9)

GB

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 7

Revision: 30.05.2017

Trade name: **CHOKE & CARBURATOR CLEANER NEW**

(Contd. of page 8)

· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Reg. (EC) n. 1272/2008 - CLP;
 Reg. (EC) n. 1907/2006 – Reach;
 Reg. (EC) n. 2015/830 annex II of REACH;
 Reg. (EC) n. 648/04 (Detergents);
 Reg. (EC) n. 528/12 (Biocides BPR);
 Reg. (EC) n. 1223/2009 (Cosmetics);
 Dir. 06/08 ADR – RID - IMDG - IATA;
 Dir. 47/08 (Aerosols); Dir. 12/18 (Seveso III);
 Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	75-100

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H280 Contains gas under pressure; may explode if heated.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:**

Customer Service
 NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710
 B: Tel: +32 2 347 0117 Fax: +32 2 347 1395
 IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61
 UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· **Contact:**

(Contd. on page 10)

Safety data sheet
According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 7

Revision: 30.05.2017

Trade name: CHOKE & CARBURATOR CLEANER NEW

(Contd. of page 9)

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**