

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 6

Revision: 30.05.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **ERASE NEW**

Article number: 03110001

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Paint remover

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

ZEP UK Ltd
Tanhouse Lane
Widnes Cheshire, WA8 0RR
United Kingdom
Tel: +44 (0)151 422 1000
Fax: +44 (0)151 422 1011
@: info@zep.co.uk
web: www.zep.co.uk

ZEP Industries BV
Vierlinghweg 30
4612 PN Bergen op Zoom
The Netherlands
Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117
Fax: (NL) + 31 164 266 710 (B) + 32 2 347 1395
@: sales@zepbenelux.com

ZEP ITALIA SRL
Via Netunese Km. 25.000
04011 Aprilia (LT) - Italy
Tel: +39.06.926691
Fax: +39.06.92747061
@: tecnico@zepeurope.com
Sito: www.zep.it

Further information obtainable from:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

1.4 Emergency telephone number:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

GB

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 6

Revision: 30.05.2017

Trade name: ERASE NEW

(Contd. of page 1)

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02

GHS07

GHS09

Signal word Danger**Hazard-determining components of labelling:***(R)-p-mentha-1,8-diene*

ethyl acetate

acetone

Hazard statementsH222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*H315 *Causes skin irritation.*H319 *Causes serious eye irritation.*H317 *May cause an allergic skin reaction.*H336 *May cause drowsiness or dizziness.*H411 *Toxic to aquatic life with long lasting effects.***Precautionary statements**P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*P251 *Do not pierce or burn, even after use.*P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*P301+P310 *IF SWALLOWED: Immediately call a POISON CENTER/ doctor.*P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.***2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2219471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 5989-27-5 EINECS: 227-813-5 Reg.nr.: 01-2119529223-47	<i>(R)-p-mentha-1,8-diene</i> ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Skin Irrit. 2, H315; Skin Sens. 1B, H317	10-25%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol ⚠ Flam. Liq. 2, H225	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1, H220 Press. Gas C, H280	2.5-5%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1, H220 Press. Gas C, H280	2.5-5%

(Contd. on page 3)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 6

Revision: 30.05.2017

Trade name: ERASE NEW

(Contd. of page 2)

CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 012119486944-21-xxxx	propane ⚠ Flam. Gas 1, H220 Press. Gas C, H280	2.5-5%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide ⚠ Press. Gas D, H280	2.5-5%

· **Ingredients according to Detergents Regulation 648/2004/EC** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Seek immediate medical advice.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.

(Contd. on page 4)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 6

Revision: 30.05.2017

Trade name: ERASE NEW

(Contd. of page 3)

- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate (10-25%)

WEL (Great Britain)	Short-term value: 400 ppm Long-term value: 200 ppm
---------------------	---

67-64-1 acetone (10-25%)

WEL (Great Britain)	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
IOELV (European Union)	Long-term value: 1210 mg/m ³ , 500 ppm

64-17-5 ethanol (10-25%)

WEL (Great Britain)	Long-term value: 1920 mg/m ³ , 1000 ppm
---------------------	--

106-97-8 butane (2.5-5%)

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
---------------------	---

124-38-9 carbon dioxide (2.5-5%)

WEL (Great Britain)	Short-term value: 27400 mg/m ³ , 15000 ppm Long-term value: 9150 mg/m ³ , 5000 ppm
IOELV (European Union)	Long-term value: 9000 mg/m ³ , 5000 ppm

· **DNELs**

67-64-1 acetone

Oral	DNEL Long term-systemic	62 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	62 mg/kg human/day (consumer)
		186 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m ³	200 mg/m ³ (consumer)
		1210 mg/m ³ (worker)
	DNEL Acute-local mg/m ³	2420 mg/m ³ (worker)

5989-27-5 (R)-p-mentha-1,8-diene

Oral	DNEL acute-systemic	4.76 mg/kg human/day (consumer)
Inhalative	DNEL Acute-systemic mg/m ³	33.3 mg/m ³ (worker)

64-17-5 ethanol

Oral	DNEL Long term-systemic	87 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	206 mg/kg human/day (consumer)
		343 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m ³	114 mg/m ³ (consumer)
		950 mg/m ³ (worker)
	DNEL Long term local mg/m ³	950 mg/m ³ (consumer) 1900 mg/m ³ (worker)

· **PNECs**

67-64-1 acetone

PNEC Freshwater mg/L	10.6 mg/L
PNEC Marinewater mg/L	1.06 mg/L
PNEC Marine water sediment	3.04 mg/Kg
PNEC Intermittent release	21 (mg/L)
PNEC Soil	33.3 mg/Kg

(Contd. on page 5)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 6

Revision: 30.05.2017

Trade name: ERASE NEW

(Contd. of page 4)

64-17-5 ethanol

PNEC Freshwater mg/L	0.96 mg/L (-)
PNEC Marinewater mg/L	0.79 mg/L (-)
PNEC Freshwater sediment	3.6 mg/Kg (-)
PNEC Marine water sediment	2.9 mg/Kg (-)
PNEC Intermittent release	2.75 mg/l (-)
PNEC Soil	0.63 mg/Kg (-)
PNEC Sewage treatment Plant mg/L	580 mg/L (-)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Filter AX

· **Protection of hands:**



Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· **Not suitable are gloves made of the following materials:** Strong material gloves

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:** Aerosol

· **Colour:** Colourless

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· **Melting point/freezing point:** Undetermined.

· **Initial boiling point and boiling range:** 55 °C

· **Flash point:** < 0 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 255 °C

· **Decomposition temperature:** Not determined.

(Contd. on page 6)

GB

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 6

Revision: 30.05.2017

Trade name: ERASE NEW

(Contd. of page 5)

· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	15.0 Vol %
· Vapour pressure at 20 °C:	233 hPa
· Density at 20 °C:	0.791 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Insoluble.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	94.3 %
EU-VOC:	751.3 g/l
EU-VOC	94.60 %
Swiss VOC:	72.60 %
Solids content:	0.5 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

141-78-6 ethyl acetate

Oral	LD50	4935 mg/kg (Rabbit)
Dermal	LD50	>18000 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	1600 mg/ltr (Rat)
	EC50 / 24 h	2500 mg/ltr (Daphnia magna (water flea))

67-64-1 acetone

Oral	LD50	>3000 mg/kg (Mouse)
		5800 mg/kg (Rat)
		>5000 mg/kg (Rabbit)
Dermal	LD50	>15800 mg/kg (Rat)
		>15000 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	76 mg/ltr (Rat)
	LC50 / 48 h	2262 mg/ltr (Daphnia magna (water flea))
	LC50 / 96 h (static)	5540 mg/ltr (fish)

(Contd. on page 7)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 6

Revision: 30.05.2017

Trade name: ERASE NEW

(Contd. of page 6)

	EC 50 / 48 h	100 mg/ltr (<i>Pimephales promelas</i>) 8800 mg/ltr (<i>Daphnia magna</i> (water flea))
5989-27-5 (R)-p-mentha-1,8-diene		
Oral	LD50	4400 mg/kg (Rat)
Dermal	LD50	>5000 mg/kg (Rat) >2000 mg/kg (Rabbit)
	EC50	34.1 mg/ltr (<i>Daphnia magna</i> (water flea))
64-17-5 ethanol		
Oral	LD50	7060 mg/kg (Rat)
Inhalative	LC50 / 4 h	20000 mg/ltr (Rat)
	EC 50 / 48 h	10800 mg/ltr (<i>Daphnia magna</i> (water flea))
106-97-8 butane		
Inhalative	LC50 / 4 h	658 mg/ltr (Rat)

- **Primary irritant effect:**

- **Skin corrosion/irritation**

Causes skin irritation.

- **Serious eye damage/irritation**

Causes serious eye irritation.

- **Respiratory or skin sensitisation**

May cause an allergic skin reaction.

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

- **Carcinogenicity** Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.

- **STOT-single exposure**

May cause drowsiness or dizziness.

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

- **Aspiration hazard**

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

67-64-1 acetone

COD	2.21 (mg O ₂ / g product)
-----	--------------------------------------

5989-27-5 (R)-p-mentha-1,8-diene

OECD test 301 D	>92 (biodegradation in % after 28 days)
-----------------	---

- **12.2 Persistence and degradability** No further relevant information available.

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Toxic for fish

- **Additional ecological information:**

- **General notes:**

The surfactant(s) contained in this preparation complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 8)

Safety data sheet
According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 6

Revision: 30.05.2017

Trade name: ERASE NEW

(Contd. of page 7)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations

· **European waste catalogue**

20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 40	metals

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA**

UN1950

· **14.2 UN proper shipping name**

· **ADR**

· **IMDG**

· **IATA**

1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (DIPENTENE), MARINE POLLUTANT AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**

2 5F Gases.

· **Label**

2.1

· **IMDG**



· **Class**

2.1

· **Label**

2.1

· **IATA**



· **Class**

2.1

· **Label**

2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA**

Void

· **14.5 Environmental hazards:**

Product contains environmentally hazardous substances: (R)-p-mentha-1,8-diene

· **Marine pollutant:**

Yes

· **Special marking (ADR):**

Symbol (fish and tree)
Symbol (fish and tree)

· **14.6 Special precautions for user**

Warning: Gases.

· **Danger code (Kemler):**

-

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:

(Contd. on page 9)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 6

Revision: 30.05.2017

Trade name: ERASE NEW

(Contd. of page 8)

· **Segregation Code**

Category A. For AEROSOLS with a capacity above 1 litre:
 Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
 SG69 For AEROSOLS with a maximum capacity of 1 litre:
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre:
 Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **Transport category**

2

· **Tunnel restriction code**

D

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Reg. (EC) n. 1272/2008 - CLP;

Reg. (EC) n. 1907/2006 – Reach;

Reg. (EC) n. 2015/830 annex II of REACH;

Reg. (EC) n. 648/04 (Detergents);

Reg. (EC) n. 528/12 (Biocides BPR);

Reg. (EC) n. 1223/2009 (Cosmetics);

Dir. 06/08 ADR – RID - IMDG - IATA;

Dir. 47/08 (Aerosols); Dir. 12/18 (Seveso III);

Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	75-100

· **Waterhazard class:** Water danger class 3 (Self-assessment): extremely hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

(Contd. on page 10)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 30.05.2017

Version: 6

Revision: 30.05.2017

Trade name: ERASE NEW

(Contd. of page 9)

*H280 Contains gas under pressure; may explode if heated.**H304 May be fatal if swallowed and enters airways.**H315 Causes skin irritation.**H317 May cause an allergic skin reaction.**H319 Causes serious eye irritation.**H336 May cause drowsiness or dizziness.**H400 Very toxic to aquatic life.**H410 Very toxic to aquatic life with long lasting effects.***· Department issuing SDS:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· Contact:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· Abbreviations and acronyms:*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonised System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)**VOC: Volatile Organic Compounds (USA, EU)**DNEL: Derived No-Effect Level (REACH)**PNEC: Predicted No-Effect Concentration (REACH)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Flam. Gas 1: Flammable gases – Category 1**Aerosol 1: Aerosols – Category 1**Press. Gas C: Gases under pressure – Compressed gas**Press. Gas D: Gases under pressure – Dissolved gas**Flam. Liq. 2: Flammable liquids – Category 2**Flam. Liq. 3: Flammable liquids – Category 3**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**Skin Sens. 1B: Skin sensitisation – Category 1B**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2***· * Data compared to the previous version altered.**

GB