

**Safety data sheet**  
According to 1907/2006/EC, Article 31 REACH

Printing date 17.04.2018

Version: 6

Revision: 17.04.2018

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· **Trade name:** **ZEPOXY METAL PRIMER GREY**

· **Article number:** 54640001

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category**

PROC7 Industrial spraying

PROC10 Roller application or brushing

PROC11 Non industrial spraying

· **Environmental release category**

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

· **Application of the substance / the mixture** Coating compound/ Surface coating/ paint

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

ZEP UK Ltd  
Tanhouse Lane  
Widnes Cheshire, WA8 0RR  
United Kingdom  
Tel: +44 (0)151 422 1000  
Fax: +44 (0)151 422 1011  
@: info@zep.co.uk  
web: www.zep.co.uk

ZEP Industries BV  
Vierlingweg 30  
4612 PN Bergen op Zoom  
The Netherlands  
Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117  
Fax: (NL) + 31 164 266 710 (B) + 32 2 347 1395  
@: sales@zепенelux.com

ZEP ITALIA SRL  
Via Netunese Km. 25.000  
04011 Aprilia (LT) - Italy  
Tel: +39.06.926691  
Fax: +39.06.92747061  
@: tecnico@zepeurope.com  
Sito: www.zep.it

· **Further information obtainable from:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· **1.4 Emergency telephone number:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

(Contd. on page 2)

GB

# Safety data sheet

## According to 1907/2006/EC, Article 31 REACH

Printing date 17.04.2018

Version: 6

Revision: 17.04.2018

Trade name: **ZEPOXY METAL PRIMER GREY**

(Contd. of page 1)

Eye Dam. 1 H318 Causes serious eye damage.  
Skin Sens. 1 H317 May cause an allergic skin reaction.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS02

GHS05

GHS07

**Signal word** Danger**Hazard-determining components of labelling:**

Poly(bisphenol A-co-epichlorohydrin) glycidyl end-capped

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

**Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards** The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.**Results of PBT and vPvB assessment**• **PBT:** Not applicable.• **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures**• **Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene (mix) ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-10%
CAS: 25036-25-3	Poly(bisphenol A-co-epichlorohydrin) glycidyl end-capped ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	5-10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2.5-5%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38-xxxx	butanol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	2.5-5%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	2.5-5%
CAS: 68082-29-1 NLP: 500-191-5	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	1-2.5%

• **Ingredients according to Detergents Regulation 648/2004/EC** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

# Safety data sheet

## According to 1907/2006/EC, Article 31 REACH

Printing date 17.04.2018

Version: 6

Revision: 17.04.2018

Trade name: ZEPOXY METAL PRIMER GREY

(Contd. of page 2)

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**  
If skin irritation continues, consult a doctor.  
Immediately wash with water and soap and rinse thoroughly.  
Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information** Cool endangered receptacles with water spray.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation
- **6.2 Environmental precautions:**  
Prevent seepage into sewage system, workpits and cellars.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, universal binders).  
Use neutralising agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.  
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Provide solvent resistant, sealed floor.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

# Safety data sheet

## According to 1907/2006/EC, Article 31 REACH

Printing date 17.04.2018

Version: 6

Revision: 17.04.2018

Trade name: ZEPOXY METAL PRIMER GREY

(Contd. of page 3)

### SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**1330-20-7 xylene (mix) (5-10%)**

WEL (Great Britain)	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
---------------------	--

IOELV (European Union)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin
------------------------	--

**108-65-6 2-methoxy-1-methylethyl acetate (2.5-5%)**

WEL (Great Britain)	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm Sk
---------------------	--

IOELV (European Union)	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 275 mg/m <sup>3</sup> , 50 ppm Skin
------------------------	--

**71-36-3 butanol (2.5-5%)**

WEL (Great Britain)	Short-term value: 154 mg/m <sup>3</sup> , 50 ppm Sk
---------------------	--

**123-86-4 n-butyl acetate (2.5-5%)**

WEL (Great Britain)	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
---------------------	---

**100-41-4 ethylbenzene (0.1-1%)**

WEL (Great Britain)	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
---------------------	---

IOELV (European Union)	Short-term value: 884 mg/m <sup>3</sup> , 200 ppm Long-term value: 442 mg/m <sup>3</sup> , 100 ppm Skin
------------------------	---

· **DNELs**

**108-65-6 2-methoxy-1-methylethyl acetate**

Oral	DNEL Long term-systemic	1.67 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	54.8 mg/kg human/day (consumer)
		153.5 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m <sup>3</sup>	33 mg/m <sup>3</sup> (consumer)
		275 mg/m <sup>3</sup> (worker)

· **PNECs**

**108-65-6 2-methoxy-1-methylethyl acetate**

PNEC Freshwater mg/L	0.635 mg/L
PNEC Freshwater sediment	3.29 mg/Kg
PNEC Marine water sediment	0.329 mg/Kg
PNEC Soil	0.29 mg/Kg
PNEC Sewage treatment Plant mg/L	100 mg/L

· **Ingredients with biological limit values:**

**1330-20-7 xylene (mix) (5-10%)**

BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
----------------------	--

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

## Safety data sheet

### According to 1907/2006/EC, Article 31 REACH

Printing date 17.04.2018

Version: 6

Revision: 17.04.2018

**Trade name: ZEPOXY METAL PRIMER GREY**

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.

- **Respiratory protection:** Not required.
- **Protection of hands:**



Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- **For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

PVA gloves

- **Not suitable are gloves made of the following materials:** Strong material gloves

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Solvent resistant protective clothing

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Fluid

**Colour:** According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

- **Change in condition**

**Melting point/freezing point:** Undetermined.

**Initial boiling point and boiling range:** 137 °C

· **Flash point:** 27 °C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 500 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Product does not present an explosion hazard.

- **Explosion limits:**

**Lower:** 1.1 Vol %

**Upper:** 7 Vol %

· **Vapour pressure at 20 °C:** 6.7 hPa

· **Density at 20 °C:** 1.44 g/cm<sup>3</sup>

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

(Contd. on page 6)

# Safety data sheet

## According to 1907/2006/EC, Article 31 REACH

Printing date 17.04.2018

Version: 6

Revision: 17.04.2018

Trade name: ZEPOXY METAL PRIMER GREY

(Contd. of page 5)

· <b>Solubility in / Miscibility with water:</b>	Insoluble.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	20.0 %
<b>EU-VOC:</b>	495.0 g/l
<b>EU-VOC</b>	34.40 %
<b>Swiss VOC:</b>	34.38 %
· <b>Solids content:</b>	69.0 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### 1330-20-7 xylene (mix)

Oral	LD50	4,300 mg/kg (Rat)
Dermal	LD50	2,000 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	6,350 mg/ltr (Rat)
	LC50 / 96 h	3.77-13.5 mg/ltr (fish)
	EC 50 / 48 h	7.4 mg/ltr (Daphnia magna (water flea))

##### 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rat)
	LC50 / 96 h	100-180 mg/ltr (Oncorhynchus mykiss (Rainbow trout))
	EC 50 / 48 h	373 mg/ltr (Daphnia magna (water flea))

##### 71-36-3 butanol

Oral	LD50	790 mg/kg (Rat)
Dermal	LD50	3,400 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	8,000 mg/ltr (Rat)
	EC 50 / 48 h	1,983 mg/ltr (Daphnia magna (water flea))
	EC 50 / 72 H	8,500 (Selenastrum capricornutum (Algae)) mg/l

##### 123-86-4 n-butyl acetate

Oral	LD50	10,770 mg/kg (Rat)
Dermal	LD50	>17,600 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	>21 mg/ltr (Rat)
	LC50/ 24 h	205 mg/ltr (Daphnia magna (water flea))
	EC 50 / 96 h	320 mg/ltr (Selenastrum capricornutum (Algae))

(Contd. on page 7)

# Safety data sheet

## According to 1907/2006/EC, Article 31 REACH

Printing date 17.04.2018

Version: 6

Revision: 17.04.2018

Trade name: ZEPOXY METAL PRIMER GREY

(Contd. of page 6)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye damage.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.


### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Must not reach sewage water or drainage ditch undiluted or unneutralised.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Disposal must be made according to official regulations
- **Uncleaned packaging:**
- **Recommendation:** Disposal in accordance with administrative provisions

### SECTION 14: Transport information

- |   |                           |
|---|---------------------------|
| · <b>14.1 UN-Number</b>   |                           |
| · <b>ADR, IMDG, IATA</b>  | UN1263                    |
| · <b>14.2 UN proper shipping name</b>   |                           |
| · <b>ADR</b>  | 1263 PAINT                |
| · <b>IMDG, IATA</b>   | PAINT                     |
| · <b>14.3 Transport hazard class(es)</b>  |                           |
| · <b>ADR</b>  |                           |
|  |                           |
| · <b>Class</b>  | 3 (F1) Flammable liquids. |
| · <b>Label</b>  | 3                         |

(Contd. on page 8)

GB

# Safety data sheet

## According to 1907/2006/EC, Article 31 REACH

Printing date 17.04.2018

Version: 6

Revision: 17.04.2018

Trade name: ZEPOXY METAL PRIMER GREY

(Contd. of page 7)

· **IMDG, IATA**

· **Class** 3 Flammable liquids.  
 · **Label** 3

· **14.4 Packing group**  
 · **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**  
 · **Marine pollutant:** No

· **14.6 Special precautions for user** Warning: Flammable liquids.  
 · **Danger code (Kemler):** 30  
 · **EMS Number:** F-E,S-E  
 · **Stowage Category** A

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**  
 · **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml  
 · **Transport category** 3  
 · **Tunnel restriction code** D/E

· **IMDG**  
 · **Limited quantities (LQ)** 5L  
 · **Excepted quantities (EQ)** Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN 1263 PAINT, 3, III

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Reg. (EC) n. 1272/2008 - CLP;  
 Reg. (EC) n. 1907/2006 – Reach;  
 Reg. (EC) n. 2015/830 annex II of REACH;  
 Reg. (EC) n. 648/04 (Detergents);  
 Reg. (EC) n. 528/12 (Biocides BPR);  
 Reg. (EC) n. 1223/2009 (Cosmetics);  
 Dir. 06/08 ADR – RID - IMDG - IATA;  
 Dir. 47/08 (Aerosols); Dir. 12/18 (Seveso III);  
 Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.  
 · **Seveso category** P5c FLAMMABLE LIQUIDS  
 · **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t  
 · **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t  
 · **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **National regulations:**· **Technical instructions (air):**

Class	Share in %
NK	10-25

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

(Contd. on page 9)



# Safety data sheet

## According to 1907/2006/EC, Article 31 REACH

Printing date 17.04.2018

Version: 6

Revision: 17.04.2018

Trade name: **ZEPOXY METAL PRIMER GREY**

(Contd. of page 8)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

#### · Department issuing SDS:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

#### · Contact:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· \* **Data compared to the previous version altered.**