

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 21.11.2017

Version: 3

Revision: 21.11.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **DIG-07**

Article number: 93090001

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC35 Washing and cleaning products (including solvent based products)

Process category

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC11 Non industrial spraying

Uses advised against Cleaning agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

ZEP UK Ltd

Tanhouse Lane

Widnes Cheshire, WA8 0RR

United Kingdom

Tel: +44 (0)151 422 1000

Fax: +44 (0)151 422 1011

@: info@zep.co.uk

web: www.zep.co.uk

ZEP Industries BV

Vierlinghweg 30

4612 PN Bergen op Zoom

The Netherlands

Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117

Fax: (NL) + 31 164 266 710 (B) + 32 2 347 1395

@: sales@zepbenelux.com

ZEP ITALIA SRL

Via Netunese Km. 25.000

04011 Aprilia (LT) - Italy

Tel: +39.06.926691

Fax: +39.06.92747061

@: tecnico@zpeurope.com

Sito: www.zep.it

Further information obtainable from:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

1.4 Emergency telephone number:

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 21.11.2017

Version: 3

Revision: 21.11.2017

Trade name: **DIG-07**

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07

Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.

Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol	Flam. Liq. 2, H225	10-25%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 110-91-8 EINECS: 203-815-1 Reg.nr.: 01-2119496057-30	morpholine	Flam. Liq. 3, H226 Acute Tox. 3, H311; Acute Tox. 3, H331 Skin Corr. 1B, H314 Acute Tox. 4, H302	1-2.5%
CAS: 9002-92-0 Reg.nr.: absent, polimer	LAURETH-4	Eye Dam. 1, H318 Aquatic Acute 1, H400	0.1-1%

Ingredients according to Detergents Regulation 648/2004/EC

For the wording of the listed hazard phrases refer to section 16.

ALCOHOL, ISOPROPYL ALCOHOL	≥15 - <30%
Nonionic surfactants	<5%
Preservation agents (METHYLISOTHIAZOLINONE)	

SECTION 4: First aid measures

4.1 Description of first aid measures

• **General information:** Immediately remove any clothing soiled by the product.

• **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

• **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:** Do not induce vomiting; call for medical help immediately.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 21.11.2017

Version: 3

Revision: 21.11.2017

Trade name: **DIG-07**

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, universal binders).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Provide solvent resistant, sealed floor.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

64-17-5 ethanol (10-25%)

WEL (Great Britain)	Long-term value: 1920 mg/m ³ , 1000 ppm
---------------------	--

67-63-0 propan-2-ol (10-25%)

WEL (Great Britain)	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
---------------------	--

(Contd. on page 4)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 21.11.2017

Version: 3

Revision: 21.11.2017

Trade name: **DIG-07**

(Contd. of page 3)

110-91-8 morpholine (1-2.5%)

<i>WEL (Great Britain)</i>	Short-term value: 72 mg/m ³ , 20 ppm Long-term value: 36 mg/m ³ , 10 ppm Sk
<i>IOELV (European Union)</i>	Short-term value: 72 mg/m ³ , 20 ppm Long-term value: 36 mg/m ³ , 10 ppm

· **DNELs****64-17-5 ethanol**

<i>Oral</i>	DNEL Long term-systemic	87 mg/kg human/day (consumer)
<i>Dermal</i>	DNEL Long term-systemic	206 mg/kg human/day (consumer) 343 mg/kg human/day (worker)
<i>Inhalative</i>	DNEL Long term-systemic mg/m ³	114 mg/m ³ (consumer) 950 mg/m ³ (worker)
	DNEL Long term local mg/m ³	950 mg/m ³ (consumer) 1,900 mg/m ³ (worker)

67-63-0 propan-2-ol

<i>Oral</i>	DNEL Long term-systemic	26 mg/kg human/day (consumer)
<i>Dermal</i>	DNEL Long term-systemic	319 mg/kg human/day (consumer) 888 mg/kg human/day (worker)
<i>Inhalative</i>	DNEL Long term-systemic mg/m ³	89 mg/m ³ (consumer) 500 mg/m ³ (worker)

· **PNECs****64-17-5 ethanol**

PNEC Freshwater mg/L	0.96 mg/L (-)
PNEC Marinewater mg/L	0.79 mg/L (-)
PNEC Freshwater sediment	3.6 mg/Kg (-)
PNEC Marine water sediment	2.9 mg/Kg (-)
PNEC Intermittent release	2.75 (-)
PNEC Soil	0.63 mg/Kg (-)
PNEC Sewage treatment Plant mg/L	580 mg/L (-)

67-63-0 propan-2-ol

PNEC Freshwater mg/L	140.9 mg/L
PNEC Marinewater mg/L	140.9 mg/L
PNEC Freshwater sediment	552 mg/Kg
PNEC Marine water sediment	552 mg/Kg
PNEC Intermittent release	140.9
PNEC Soil	28 mg/Kg

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.· **Protection of hands:**

Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 21.11.2017

Version: 3

Revision: 21.11.2017

Trade name: DIG-07

(Contd. of page 4)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- **For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

PVA gloves

- **Not suitable are gloves made of the following materials: Strong material gloves**

- **Eye protection:**



Tightly sealed goggles

- **Body protection: Solvent resistant protective clothing**

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Colour:	Colourless
Odour:	Pleasant
Odour threshold:	Not determined.

- **pH-value at 20°C:** 8.9

- **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	100°C

- **Flash point:** <55°C

- **Flammability (solid, gas):** Not applicable.

- **Ignition temperature:** 425°C

- **Decomposition temperature:** Not determined.

- **Auto-ignition temperature:** Product is not selfigniting.

- **Explosive properties:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower:	2 Vol %
Upper:	15 Vol %

- **Vapour pressure at 20°C:** 42 hPa

Density at 20°C:	0.949 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

- **Solubility in / Miscibility with water:**

Fully miscible.

- **Partition coefficient: n-octanol/water:** Not determined.

- **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

- **Solvent content:**

Organic solvents:	32.0 %
Swiss VOC:	38.00 %

(Contd. on page 6)

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 21.11.2017

Version: 3

Revision: 21.11.2017

Trade name: **DIG-07**

(Contd. of page 5)

· **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

64-17-5 ethanol

Oral	LD50	7,060 mg/kg (Rat)
Inhalative	LC50 / 4 h	20,000 mg/ltr (Rat)
	EC 50 / 48 h	10,800 mg/ltr (Daphnia magna (water flea))

67-63-0 propan-2-ol

Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	6,290 mg/kg (rab)
Inhalative	LC50 / 4 h	30 mg/ltr (Rat)
	LC50/ 8 h	12,000-19,000 mg/m3 (Rat)
	LC50 / 96 h	9,640 mg/ltr (fish)
		>1,400 mg/ltr (Lepomus gobbosus (Zonnebaars))
		6,550 mg/ltr (Pimephales promelas)
	EC50 / 24 h	>1,000 mg/ltr (Daphnia magna (water flea))
	EC 50 / 48 h	10,000 mg/ltr (Pimephales promelas)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 7)

GB

Safety data sheet
According to 1907/2006/EC, Article 31 REACH

Printing date 21.11.2017

Version: 3

Revision: 21.11.2017

Trade name: **DIG-07**



(Contd. of page 6)

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Disposal must be made according to official regulations
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1987
- **14.2 UN proper shipping name**
- **ADR** 1987 ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL), ISOPROPANOL (ISOPROPYL ALCOHOL))
- **IMDG** ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL), ISOPROPANOL (ISOPROPYL ALCOHOL))
- **IATA** ALCOHOLS, N.O.S. (ETHANOL, ISOPROPANOL (ISOPROPYL ALCOHOL))
- **14.3 Transport hazard class(es)**
- **ADR**
- 
- **Class** 3 (F) Flammable liquids.
- **Label** 3
- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids.
- **Label** 3
- **14.4 Packing group**
- **ADR, IMDG, IATA** III
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Danger code (Kemler):** 38
- **EMS Number:** F-E,S-D
- **Stowage Category** A
- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **ADR**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- **Transport category** 3
- **Tunnel restriction code** D/E

(Contd. on page 8)

GB

Safety data sheet

According to 1907/2006/EC, Article 31 REACH

Printing date 21.11.2017

Version: 3

Revision: 21.11.2017

Trade name: DIG-07

(Contd. of page 7)

· IMDG

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1987 ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL), ISOPROPANOL (ISOPROPYL ALCOHOL)), 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Reg. (EC) n. 1272/2008 - CLP;
- Reg. (EC) n. 1907/2006 – Reach;
- Reg. (EC) n. 2015/830 annex II of REACH;
- Reg. (EC) n. 648/04 (Detergents);
- Reg. (EC) n. 528/12 (Biocides BPR);
- Reg. (EC) n. 1223/2009 (Cosmetics);
- Dir. 06/08 ADR – RID - IMDG - IATA;
- Dir. 47/08 (Aerosols); Dir. 12/18 (Seveso III);
- Dir. 2008/98/CE and Reg. (EC) n.1357/2014 (Waste management)

· Directive 2012/18/EU

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· National regulations:**· Technical instructions (air):**

Class	Share in %
NK	25-50

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.

· Department issuing SDS:

- Customer Service
- NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710
- B: Tel: +32 2 347 0117 Fax: +32 2 347 1395
- IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61
- UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· Contact:

(Contd. on page 9)

GB

Safety data sheet
According to 1907/2006/EC, Article 31 REACH

Printing date 21.11.2017

Version: 3

Revision: 21.11.2017

Trade name: DIG-07

(Contd. of page 8)

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

*** Data compared to the previous version altered.**

GB