



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version: 5

Revision: 12.02.2015

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· Trade name: ERASE NEW

· Article number: EU66201

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

· Application of the substance / the mixture Paint remover

· **1.3 Details of the supplier of the safety data sheet**

· Manufacturer/Supplier:

ZEP UK Ltd

PO Box 12 Tanhouse Lane

Widnes Cheshire, WA8 ORD

United Kingdom

Phone: +44 0151 422 1000

FAX: +44 0151 422 1011

@: info@zep.co.uk

web: www.zep.co.uk

ZEP Industries BV

Vierlinghweg 30

4612 PN Bergen op Zoom

The Netherlands

Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117

Fax:(NL) + 31 164 266 710 (B) + 32 2 347 1395

@: sales@zepbenelux.com

ZEP ITALIA SRL

Via Netunese Km. 25.000

04011 Aprilia (LT) - Italy

Tel: +39.06.926691

Fax: +39.06.92747061

@: tecnico@zepeurope.com

Sito: www.zep.it

· **Further information obtainable from:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· **1.4 Emergency telephone number:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· Classification according to Regulation (EC) No 1272/2008

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version: 5

Revision: 12.02.2015

**Trade name: ERASE NEW**

(Contd. of page 1)

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xi; Irritant

R36/38: Irritating to eyes and skin.

Xi; Sensitising

R43: May cause sensitisation by skin contact.

F+; Extremely flammable

R12: Extremely flammable.

N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurised container.

Has a narcotising effect.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02

GHS07

GHS09

· **Signal word Danger**

· **Hazard-determining components of labelling:**

(R)-p-mentha-1,8-diene

ethyl acetate

acetone

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards** The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version: 5

Revision: 12.02.2015

**Trade name: ERASE NEW**

(Contd. of page 2)

| · <b>Dangerous components:</b>                                       |   |        |
|--|---|--------|
| CAS: 141-78-6<br>EINECS: 205-500-4<br>Reg.nr.: 01-2119475103-46-xxxx | ethyl acetate<br>Xi R36<br>F R11<br>R66-67<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319; STOT SE 3, H336   | 10-25% |
| CAS: 67-64-1<br>EINECS: 200-662-2<br>Reg.nr.: 01-2219471330-49-xxxx  | acetone<br>Xi R36<br>F R11<br>R66-67<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319; STOT SE 3, H336   | 10-25% |
| CAS: 5989-27-5<br>EINECS: 227-813-5<br>Reg.nr.: 01-2119529223-47     | (R)-p-mentha-1,8-diene<br>Xn R65<br>Xi R38<br>Xi R43<br>N R50/53<br>R10<br>Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>Aquatic Acute 1, H400; Aquatic Chronic 1, H410<br>Skin Irrit. 2, H315; Skin Sens. 1, H317 | 10-25% |
| CAS: 64-17-5<br>EINECS: 200-578-6<br>Reg.nr.: 01-2119457610-43-xxxx  | ethanol<br>F R11<br>Flam. Liq. 2, H225  | 10-25% |
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Reg.nr.: 01-2119474691-32-xxxx | butane<br>F+ R12<br>Flam. Gas 1, H220<br>Press. Gas C, H280   | 2.5-5% |
| CAS: 75-28-5<br>EINECS: 200-857-2<br>Reg.nr.: 01-2119485395-27-xxxx  | isobutane<br>F+ R12<br>Flam. Gas 1, H220<br>Press. Gas C, H280  | 2.5-5% |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Reg.nr.: 012119486944-21-xxxx   | propane<br>F+ R12<br>Flam. Gas 1, H220<br>Press. Gas C, H280  | 2.5-5% |
| CAS: 124-38-9<br>EINECS: 204-696-9                                   | carbon dioxide<br>Press. Gas D, H280  | 2.5-5% |

· **Ingredients according to Detergents Regulation 648/2004/EC** For the wording of the listed risk phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

· **General information:** Immediately remove any clothing soiled by the product.

#### · **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

#### · **After skin contact:**

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Seek immediate medical advice.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

· **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version: 5

Revision: 12.02.2015

**Trade name: ERASE NEW**

(Contd. of page 3)

- **For safety reasons unsuitable extinguishing agents:**  
Water  
Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.
- **Additional information** Cool endangered receptacles with water spray.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Do not seal receptacle gas tight.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

#### · 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

#### 141-78-6 ethyl acetate (10-25%)

|                     |   |
|---------------------|---|
| WEL (Great Britain) | Short-term value: 400 ppm<br>Long-term value: 200 ppm |
|---------------------|---|

#### 67-64-1 acetone (10-25%)

|                        |  |
|------------------------|--|
| WEL (Great Britain)    | Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm<br>Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm |
| IOELV (European Union) | Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm  |

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version: 5

Revision: 12.02.2015

**Trade name: ERASE NEW**

(Contd. of page 4)

**64-17-5 ethanol (10-25%)**WEL (Great Britain) Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm**106-97-8 butane (2.5-5%)**WEL (Great Britain) Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)**124-38-9 carbon dioxide (2.5-5%)**WEL (Great Britain) Short-term value: 27400 mg/m<sup>3</sup>, 15000 ppm  
Long-term value: 9150 mg/m<sup>3</sup>, 5000 ppmIOELV (European Union) Long-term value: 9000 mg/m<sup>3</sup>, 5000 ppm· **DNELs****67-64-1 acetone**

|            |   |   |
|------------|---|---|
| Oral       | DNEL Long term-systemic                   | 62 mg/kg human/day (consumer)                                       |
| Dermal     | DNEL Long term-systemic                   | 62 mg/kg human/day (consumer)                                       |
|            |   | 186 mg/kg human/day (worker)  |
| Inhalative | DNEL Acute-local mg/m <sup>3</sup>        | 2420 mg/m <sup>3</sup> (worker)                                     |
|            | DNEL Long term-systemic mg/m <sup>3</sup> | 200 mg/m <sup>3</sup> (consumer)<br>1210 mg/m <sup>3</sup> (worker) |

**5989-27-5 (R)-p-mentha-1,8-diene**

|            |                                       |                                 |
|------------|---------------------------------------|---------------------------------|
| Oral       | DNEL acute-systemic                   | 4.76 mg/kg human/day (consumer) |
| Inhalative | DNEL Acute-systemic mg/m <sup>3</sup> | 33.3 mg/m <sup>3</sup> (worker) |

**64-17-5 ethanol**

|            |   |  |
|------------|---|--|
| Oral       | DNEL Long term-systemic                   | 87 mg/kg human/day (consumer)                                      |
| Dermal     | DNEL Long term-systemic                   | 206 mg/kg human/day (consumer)                                     |
|            |   | 343 mg/kg human/day (worker)                                       |
| Inhalative | DNEL Long term local mg/m <sup>3</sup>    | 950 mg/m <sup>3</sup> (consumer)                                   |
|            |   | 1900 mg/m <sup>3</sup> (worker)                                    |
|            | DNEL Long term-systemic mg/m <sup>3</sup> | 114 mg/m <sup>3</sup> (consumer)<br>950 mg/m <sup>3</sup> (worker) |

· **PNECs****67-64-1 acetone**

|                            |                |
|----------------------------|----------------|
| PNEC Freshwater mg/L       | 10.6 mg/L (-)  |
| PNEC Intermittent release  | 21 (-) (mg/L)  |
| PNEC Marine water sediment | 3.04 mg/Kg (-) |
| PNEC Marinewater mg/L      | 1.06 mg/L (-)  |
| PNEC Soil                  | 33.3 mg/Kg (-) |

**64-17-5 ethanol**

|                                  |                |
|----------------------------------|----------------|
| PNEC Freshwater mg/L             | 0.96 mg/L (-)  |
| PNEC Freshwater sediment         | 3.6 mg/Kg (-)  |
| PNEC Intermittent release        | 2.75 mg/l (-)  |
| PNEC Marine water sediment       | 2.9 mg/Kg (-)  |
| PNEC Marinewater mg/L            | 0.79 mg/L (-)  |
| PNEC Sewage treatment Plant mg/L | 580 mg/L (-)   |
| PNEC Soil                        | 0.63 mg/Kg (-) |

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

· **Respiratory protection:** Not required.

(Contd. on page 6)

GB

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version: 5

Revision: 12.02.2015

Trade name: ERASE NEW

(Contd. of page 5)

· **Protection of hands:**



Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· **Not suitable are gloves made of the following materials:** Strong material gloves

· **Eye protection:**



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: Colourless

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 55 °C

· **Flash point:** < 0 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 255 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 2.1 Vol %

Upper: 15.0 Vol %

· **Vapour pressure at 20 °C:** 233 hPa

· **Density at 20 °C:** 0.791 g/cm<sup>3</sup>

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with water:**

Insoluble.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version: 5

Revision: 12.02.2015

**Trade name: ERASE NEW**

(Contd. of page 6)

**Kinematic:** Not determined.**· Solvent content:**

**Organic solvents:** 94.3 %  
**EU-VOC:** 751.3 g/l  
**EU-VOC** 94.60 %  
**Swiss VOC:** 72.60 %

**Solids content:** 0.5 %**· 9.2 Other information** No further relevant information available.**SECTION 10: Stability and reactivity****· 10.1 Reactivity****· 10.2 Chemical stability****· Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**· 10.3 Possibility of hazardous reactions** No dangerous reactions known.**· 10.4 Conditions to avoid** No further relevant information available.**· 10.5 Incompatible materials:** No further relevant information available.**· 10.6 Hazardous decomposition products:** No dangerous decomposition products known.**SECTION 11: Toxicological information****· 11.1 Information on toxicological effects****· Acute toxicity:****· LD/LC50 values relevant for classification:****141-78-6 ethyl acetate**

|            |             |  |
|------------|-------------|--|
| Oral       | LD50        | 4935 mg/kg (Rabbit)                      |
| Dermal     | LD50        | >18000 mg/kg (Rabbit)                    |
| Inhalative | LC50 / 4 h  | 1600 mg/ltr (Rat)                        |
|            | EC50 / 24 h | 2500 mg/ltr (Daphnia magna (water flea)) |

**67-64-1 acetone**

|            |                      |  |
|------------|----------------------|--|
| Oral       | LD50                 | >3000 mg/kg (Mouse)                      |
|            |                      | 5800 mg/kg (Rat)                         |
|            |                      | >5000 mg/kg (Rabbit)                     |
| Dermal     | LD50                 | >15800 mg/kg (Rat)                       |
|            |                      | >15000 mg/kg (Rabbit)                    |
| Inhalative | LC50 / 4 h           | 76 mg/ltr (Rat)                          |
|            | EC 50 / 48 h         | 8800 mg/ltr (Daphnia magna (water flea)) |
|            | LC50 / 48 h          | 2262 mg/ltr (Daphnia magna (water flea)) |
|            | LC50 / 96 h (static) | 5540 mg/ltr (fish)                       |
|            |                      | 100 mg/ltr (Pimephales promelas)         |

**5989-27-5 (R)-p-mentha-1,8-diene**

|        |      |  |
|--------|------|--|
| Oral   | LD50 | 4400 mg/kg (Rat)                         |
| Dermal | LD50 | >5000 mg/kg (Rat)                        |
|        |      | >2000 mg/kg (Rabbit)                     |
|        | EC50 | 34.1 mg/ltr (Daphnia magna (water flea)) |

**64-17-5 ethanol**

|            |              |   |
|------------|--------------|---|
| Oral       | LD50         | 7060 mg/kg (Rat)                          |
| Inhalative | LC50 / 4 h   | 20000 mg/ltr (Rat)                        |
|            | EC 50 / 48 h | 10800 mg/ltr (Daphnia magna (water flea)) |

**106-97-8 butane**

|            |            |                  |
|------------|------------|------------------|
| Inhalative | LC50 / 4 h | 658 mg/ltr (Rat) |
|------------|------------|------------------|

**· Primary irritant effect:****· on the skin:** Irritant to skin and mucous membranes.**· on the eye:**

Strong irritant with the danger of severe eye injury.

(Contd. on page 8)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version: 5

Revision: 12.02.2015

**Trade name: ERASE NEW**

(Contd. of page 7)

Irritating effect.

· **Sensitisation:** Sensitisation possible through skin contact.· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

**SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****67-64-1 acetone**COD 2.21 (mg O<sub>2</sub> / g product)**5989-27-5 (R)-p-mentha-1,8-diene**

OECD test 301 D &gt;92 (biodegradation in % after 28 days)

· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **Ecotoxicological effects:**· **Remark:** Toxic for fish· **Additional ecological information:**· **General notes:**

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.· **European waste catalogue**

20 00 00 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS

20 01 00 separately collected fractions (except 15 01)

20 01 40 metals

· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information**· **14.1 UN-Number**· **ADR, IMDG, IATA**

UN1950

· **14.2 UN proper shipping name**· **ADR**

1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

· **IMDG**

AEROSOLS (DIPENTENE), MARINE POLLUTANT

· **IATA**

AEROSOLS, flammable

(Contd. on page 9)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version: 5

Revision: 12.02.2015

Trade name: ERASE NEW

(Contd. of page 8)

## · 14.3 Transport hazard class(es)

## · ADR



- Class 2 5F Gases.  
· Label 2.1

## · IMDG



- Class 2.1  
· Label 2.1

## · IATA



- Class 2.1  
· Label 2.1

## · 14.4 Packing group

- ADR, IMDG, IATA Void

· 14.5 Environmental hazards: Product contains environmentally hazardous substances: (R)-p-mentha-1,8-diene

- Marine pollutant: Yes  
Symbol (fish and tree)

· Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user Warning: Gases.

- Danger code (Kemler): -  
· EMS Number: F-D,S-U

· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

## · Transport/Additional information:

## · ADR

- Limited quantities (LQ) 1L  
· Excepted quantities (EQ) Code: E0  
Not permitted as Excepted Quantity

· Transport category 2

· Tunnel restriction code D

## · IMDG

- Limited quantities (LQ) 1L  
· Excepted quantities (EQ) Code: E0  
Not permitted as Excepted Quantity

· UN "Model Regulation": UN1950, AEROSOLS, ENVIRONMENTALLY HAZARDOUS, 2.1

GB

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version: 5

Revision: 12.02.2015

**Trade name: ERASE NEW**

(Contd. of page 9)

**SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **National regulations:**

· **Technical instructions (air):**

| Class | Share in % |
|-------|------------|
| NK    | 75-100     |

· **Waterhazard class:** Water danger class 3 (Self-assessment): extremely hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

R10 Flammable.

R11 Highly flammable.

R12 Extremely flammable.

R36 Irritating to eyes.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· **Contact:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 12.02.2015

Version: 5

Revision: 12.02.2015

**Trade name: ERASE NEW**

(Contd. of page 10)

*Press. Gas D: Gases under pressure: Dissolved gas*  
*Flam. Liq. 2: Flammable liquids, Hazard Category 2*  
*Flam. Liq. 3: Flammable liquids, Hazard Category 3*  
*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*  
*Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2*  
*Skin Sens. 1: Sensitisation - Skin, Hazard Category 1*  
*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*  
*Asp. Tox. 1: Aspiration hazard, Hazard Category 1*  
*Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1*  
*Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1*  
*Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2*  
· **\* Data compared to the previous version altered.**

GB