



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.09.2014

Version: 4

Revision: 09.09.2014

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **STRIPGEL**

Article number: EU66204

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC35 Washing and cleaning products (including solvent based products)

Process category PROC10 Roller application or brushing

#### Environmental release category

ERC8a Wide dispersive indoor use of processing aids in open systems

ERC8d Wide dispersive outdoor use of processing aids in open systems

ERC8c Wide dispersive indoor use resulting in inclusion into or onto a matrix

ERC8f Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Application of the substance / the mixture Industrial cleaner

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

ZEP UK Ltd  
PO Box 12 Tanhouse Lane  
Widnes Cheshire, WA8 0RD  
United Kingdom  
Phone: +44 0151 422 1000  
FAX: +44 0151 422 1011  
@: info@zep.co.uk  
web: www.zep.co.uk

ZEP Industries BV  
Vierlinghweg 30  
4612 PN Bergen op Zoom  
The Netherlands  
Tel: (NL) + 31 164 250 100 (B) + 32 2 347 0117  
Fax:(NL) + 31 164 266 710 (B) + 32 2 347 1395  
@: sales@zepbenelux.com

ZEP ITALIA SRL  
Via Netunese Km. 25.000  
04011 Aprilia (LT) - Italy  
Tel: +39.06.926691  
Fax: +39.06.92747061  
@: tecnico@zepeurope.com  
Sito: www.zep.it

#### Further information obtainable from:

Customer Service  
NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710  
B: Tel: +32 2 347 0117 Fax: +32 2 347 1395  
IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61  
UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

### 1.4 Emergency telephone number:

Customer Service  
NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710  
B: Tel: +32 2 347 0117 Fax: +32 2 347 1395  
IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61  
UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Carc. 2 H351 Suspected of causing cancer.

STOT SE 1 H370-H335-H336 Causes damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Skin Irrit. 2 H315 Causes skin irritation.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 09.09.2014

Version: 4

Revision: 09.09.2014

**Trade name: STRIPGEL**

(Contd. of page 1)

Eye Irrit. 2 H319 Causes serious eye irritation.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

T; Toxic

R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

Xn; Harmful

R20/21/22-40: Harmful by inhalation, in contact with skin and if swallowed. Limited evidence of a carcinogenic effect.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The substance is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

dichloromethane

methanol

· **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H370-H335-H336 Causes damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P362 Take off contaminated clothing and wash before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Can become highly flammable in use.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

(Contd. on page 3)

GB

# Safety data sheet

according to 1907/2006/EC, Article 31

















Printing date 09.09.2014

Version: 4

Revision: 09.09.2014

Trade name: **STRIPGEL**

(Contd. of page 2)

CAS: 75-09-2 EINECS: 200-838-9 Reg.nr.: 01-2119480404-41	dichloromethane  Xn R40  Xi R36/37/38 R67 Carc. Cat. 3  Carc. 2, H351; STOT RE 2, H373  Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335-H336	75-100%
CAS: 67-56-1 EINECS: 200-659-6 Reg.nr.: 01-2119433307-44	methanol  T R23/24/25-39/23/24/25  F R11  Flam. Liq. 2, H225  Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331  STOT SE 1, H370	10-25%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-0004	Hydrocarbons, C9, Aromatics  Xn R65  Xi R37  N R51/53 R10-66-67  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H335-H336	0.1-1%

· **Ingredients according to Detergents Regulation 648/2004/EC** For the wording of the listed risk phrases refer to section 16.

## SECTION 4: First aid measures

### · 4.1 Description of first aid measures

#### · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

#### · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

#### · After swallowing:

Do not induce vomiting; call for medical help immediately.

Call for a doctor immediately.

#### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### · 5.1 Extinguishing media

· **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

### · 5.3 Advice for firefighters

· **Protective equipment:** Mount respiratory protective device.

#### · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## SECTION 6: Accidental release measures

### · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.09.2014

Version: 4

Revision: 09.09.2014

**Trade name: STRIPGEL**

(Contd. of page 3)

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Use only in well ventilated areas.

· **Information about fire - and explosion protection:** Keep ignition sources away - Do not smoke.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Provide solvent resistant, sealed floor.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**75-09-2 dichloromethane (75-100%)**

WEL (Great Britain)	Short-term value: 1060 mg/m <sup>3</sup> , 300 ppm Long-term value: 350 mg/m <sup>3</sup> , 100 ppm BMGV, Sk
---------------------	--

**67-56-1 methanol (10-25%)**

WEL (Great Britain)	Short-term value: 333 mg/m <sup>3</sup> , 250 ppm Long-term value: 266 mg/m <sup>3</sup> , 200 ppm Sk
IOELV (European Union)	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin

· **DNELs**

**75-09-2 dichloromethane**

Oral	DNEL Long term-systemic	0.06 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	2395 mg/kg human/day (consumer)
		4750 mg/kg human/day (worker)
Inhalative	DNEL Acute-systemic mg/m <sup>3</sup>	353 mg/m <sup>3</sup> (consumer)
		706 mg/m <sup>3</sup> (worker)
	DNEL Long term-systemic mg/m <sup>3</sup>	88.3 mg/m <sup>3</sup> (consumer)
		353 mg/m <sup>3</sup> (worker)

**67-56-1 methanol**

Oral	DNEL Long term-systemic	8 mg/kg human/day (consumer)
	DNEL acute-systemic	8 mg/kg human/day (consumer)
Dermal	DNEL Acute-systemic	8 mg/kg human/day (consumer)
		40 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic	8 mg/kg human/day (consumer)
		40 mg/kg human/day (worker)
	DNEL Acute-local mg/m <sup>3</sup>	50 mg/m <sup>3</sup> (consumer)

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.09.2014

Version: 4

Revision: 09.09.2014

**Trade name: STRIPGEL**

(Contd. of page 4)

	DNEL Acute-systemic mg/m <sup>3</sup>	260 mg/m <sup>3</sup> (worker) 50 mg/m <sup>3</sup> (consumer)
	DNEL Long term local mg/m <sup>3</sup>	260 mg/m <sup>3</sup> (worker) 50 mg/m <sup>3</sup> (consumer)
	DNEL Long term-systemic mg/m <sup>3</sup>	260 mg/m <sup>3</sup> (worker) 50 mg/m <sup>3</sup> (consumer)

**Hydrocarbons, C9, Aromatics**

Oral	DNEL Long term-systemic	11 mg/kg human/day (consumer)
Dermal	DNEL Long term-systemic	11 mg/kg human/day (consumer) 25 mg/kg human/day (worker)
Inhalative	DNEL Long term-systemic mg/m <sup>3</sup>	32 mg/m <sup>3</sup> (consumer) 100 mg/m <sup>3</sup> (worker)

**· PNECs****75-09-2 dichloromethane**

PNEC Freshwater mg/L	0.54 mg/L (-)
PNEC Freshwater sediment	4.47 mg/Kg (-)
PNEC Intermittent release	0.27 mg/L (-)
PNEC Marine water sediment	1.61 mg/Kg (-)
PNEC Marinewater mg/L	0.194 mg/L (-)
PNEC Sewage treatment Plant mg/L	26 mg/L (-)
PNEC Soil	0.583 mg/Kg (-)

**· Ingredients with biological limit values:****75-09-2 dichloromethane (75-100%)**

BMGV (Great Britain)	30 ppm Medium: end-tidal breath Sampling time: post shift Parameter: carbon monoxide
----------------------	---

· **Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

**· Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

**· Protection of hands:**

Protective gloves

**Neoprene gloves**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Neoprene gloves****· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· **Not suitable are gloves made of the following materials:** Strong material gloves

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.09.2014

Version: 4

Revision: 09.09.2014

Trade name: STRIPGEL

(Contd. of page 5)

· Eye protection:



Safety glasses

· Body protection: Solvent resistant protective clothing

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	Light yellow
Odour:	Pungent
Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	40 °C

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 455 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:	5.5 Vol %
Upper:	44.0 Vol %

· Vapour pressure at 20 °C: 453 hPa

Density at 20 °C:	1.225 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

· Solubility in / Miscibility with water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic at 20 °C:	300 s (DIN 53211/4)

· Solvent content:

Organic solvents: 98.2 %

Solids content: 1.0 %

· 9.2 Other information: No further relevant information available.

## SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions: No dangerous reactions known.

· 10.4 Conditions to avoid: No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.09.2014

Version: 4

Revision: 09.09.2014

Trade name: STRIPGEL

(Contd. of page 6)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

#### · 11.1 Information on toxicological effects

##### · Acute toxicity:

##### · LD/LC50 values relevant for classification:

###### 75-09-2 dichloromethane

Oral	LD50	1987 mg/kg (Mouse) 2136 mg/kg (Rat)
	Dermal	LD50 >2000 mg/kg (Rat)
Inhalative	LC50 / 4 h	88 mg/ltr (Rat)
	LC50 / 8 h	16189 mg/m3 (Mouse)
	EC 50 / 96 h	>662 mg/ltr (Selenastrum capricornutum (Algae))
	LC50 / 48 h (dynamic)	265 mg/ltr (Lepomis Macrochirus (Bluegill Sunfish)) 265 mg/ltr (Pimephales promelas)
	LC50 / 96 h (static)	310 mg/ltr (Lepomis Macrochirus (Bluegill Sunfish)) 330 mg/ltr (Cyprinodon Variegatus) 193 mg/ltr (Pimephales promelas)
	LC50 / 24 h (dynamic)	268 mg/ltr (Lepomis Macrochirus (Bluegill Sunfish)) 310 mg/ltr (Daphnia magna (water flea)) 268 mg/ltr (Pimephales promelas)

###### 67-56-1 methanol

Oral	LD50	>5000 mg/kg (Rat)
Dermal	LD50	20000 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	80-130 mg/ltr (Rat)
	EC50 / 24 h	>10000 mg/ltr (Daphnia magna (water flea))
	LC50 / 96 h	>10000 mg/ltr (fish)

###### Hydrocarbons, C9, Aromatics

Oral	LD50	3592 mg/kg (Rat)
Dermal	LD50	>3160 mg/kg (Rabbit)
Inhalative	LC50 / 4 h	>6193 mg/ltr (Rat)

##### · Primary irritant effect:

· on the skin: Irritant to skin and mucous membranes.

##### · on the eye:

Strong irritant with the danger of severe eye injury.

Irritating effect.

· Sensitization: No sensitizing effects known.

##### · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carc. 2

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

###### Hydrocarbons, C9, Aromatics

EL50 (48 h) 3.2 mg/l (Daphnia magna (water flea))

· 12.2 Persistence and degradability No further relevant information available.

· Other information: The product is difficultly biodegradable.

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.09.2014

Version: 4

Revision: 09.09.2014

**Trade name: STRIPGEL**

(Contd. of page 7)

**Additional ecological information:****General notes:**

Water danger class 3 (German Regulation) (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.

**12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**European waste catalogue**

15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 04	metallic packaging
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 17*	wastes from paint or varnish removal containing organic solvents or other dangerous substances

**Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information****14.1 UN-Number**

· **ADR, IMDG, IATA** UN2810

**14.2 UN proper shipping name**

· **ADR** 2810 TOXIC LIQUID, ORGANIC, N.O.S. (METHANOL, DICHLOROMETHANE)  
· **IMDG, IATA** TOXIC LIQUID, ORGANIC, N.O.S. (METHANOL, DICHLOROMETHANE)

**14.3 Transport hazard class(es)****ADR**

· **Class** 6.1 (T1) Toxic substances.  
· **Label** 6.1

**IMDG, IATA**

· **Class** 6.1 Toxic substances.  
· **Label** 6.1

**14.4 Packing group**

· **ADR, IMDG, IATA** III

**14.5 Environmental hazards:**

· **Marine pollutant:** No

**14.6 Special precautions for user**

· **Danger code (Kemler):** Warning: Toxic substances.

60

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.09.2014

Version: 4

Revision: 09.09.2014

**Trade name: STRIPGEL**

(Contd. of page 8)

· <b>EMS Number:</b>	F-A,S-A
· <b>Segregation groups</b>	Liquid halogenated hydrocarbons
· <b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN2810, TOXIC LIQUID, ORGANIC, N.O.S. (METHANOL, DICHLOROMETHANE), 6.1, III

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
I	75-100

· **Waterhazard class:** Water danger class 3 (Self-assessment): extremely hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
R10	Flammable.
R11	Highly flammable.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R36/37/38	Irritating to eyes, respiratory system and skin.
R37	Irritating to respiratory system.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R40	Limited evidence of a carcinogenic effect.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.09.2014

Version: 4

Revision: 09.09.2014

**Trade name: STRIPGEL**

(Contd. of page 9)

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

**· Department issuing MSDS:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

**· Contact:**

Customer Service

NL: Tel: + 31 164 250 100 Fax: + 31 164 266 710

B: Tel: +32 2 347 0117 Fax: +32 2 347 1395

IT: Tel: +39 069 266 91 Fax: +39 06.927 470 61

UK: Tel: +44 151 422 1000 Fax: +44 151 422 1011

**· Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 3: Acute toxicity, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

**· \* Data compared to the previous version altered.**

GB