



Product Specification Report

1.0/03120005/0719

Quickly and permanently dissolves most commercially available gaskets.

STRIPGEL

Fast acting solvent for gaskets

FEATURES:

Efficient	Highly penetrating, effective in removing gaskets, also those present since a long time
Easy application	Can be applied with a paintbrush, covering the surfaces with a thin layer of product
Easy to rinse	Can be rinsed quickly with water
Safe on surfaces	Does not affect light alloys
Gel formula	Can be used on wood, cement and metals, thanks to its gel formula it is particularly suitable for vertical surfaces
No flash point	Has no flash point, according to European normative NF EN 22719

SPECIFICATIONS:

Form Viscous gel
 Colour Yellow-Orange
 Odour..... Pungent
 Flash point Non applicable
 Density at 20°C..... 1,22 g/cm³
 Solubility in water Soluble

COMPATIBILITY:

Can be used on wood, iron, cement on vertical surfaces, inside as well as outside. When used on wood, if necessary, polish after the removal of paint. On other materials it can be necessary to clean with a solvent before going ahead with other paint treatments.

ACTIVE INGREDIENTS:

- Dichloromethane
- Methanol

INSTRUCTIONS FOR USE:

MANUALLY: apply Stripgel with a paintbrush on the surface. Let it act for 15-20 minutes. To remove gaskets use a scraper, or, for better results, use a pressure washer. **IMMERSION:** immerse the piece to be treated in the undiluted product. A container in stainless steel is recommended. Let it act for 10 minutes and empty the container. Rinse the piece(s) with a pressure washer for better results.

PRECAUTIONS FOR USE:

Attention the product also acts as a paint-stripper for most paints available on the market. When the product is used at a temperature below 15°C (59°F), the product should be mixed thoroughly before use. For more information consult the safety data sheet.

All information in this document is based on our practical experience and/or laboratory tests. Due to the multiplicity of conditions for usage and variable human factors, we recommend that you always test our products for suitability prior to use. At any time, this version of the product specification report may have been revised based on legislation, availability of the individual ingredients or newly acquired information. The current approved version is available upon request.



Zep UK Ltd.
 T • 0151 422 1000
 F • 0151 422 1011
 info@zep.co.uk
 www.zep.co.uk



Zep Italia s.r.l.
 T • 800 016 918
 Numero Verde Tecnico
 800-579185
 tecnico@zepeurope.com
 www.zep.it



Zep Industries BV
 T • 02 347 01 17
 F • 02 347 13 95
 sales@zep.be
 www.zepindustries.be



Zep Industries BV
 T • 0164 250100
 F • 0164 266710
 info@zepbenelux.com
 www.zepindustries.nl



Zep Industries BV
 T • 0521 174158
 F • 0521 5217114
 sales@zepbenelux.com
 www.zepindustries.de