



Product Specification Report

1.2/98050003/1116

Specifically formulated to remove residual acidity after descaling with acid products or to alkalize the water used in steam generators.

BOILER ALK

Alkalizing treatment for steam generators

CARATTERISTICHE:

Concentrated	Effective at low dosages. Quickly neutralises acid pH values.
Safe	Does not contain volatile substances which makes it suitable for use in places where high purity of the steam is required.

INSTRUCTIONS FOR USE:

The product can be dosed automatically on-line or in the accumulation tank of the steam generator. Optimal dosing can be realised with the use of a dosing pump linked to the pump of the feed water. Ideal dosage varies depending on the characteristics and temperature of the water in the system. The pH of the water should be monitored. Depending on the pressure in the system, the pH of the water should be between 9 and 12.

PRECAUTIONS FOR USE:

For more information, consult the MSDS.

APPROVALS:

The active ingredients in the product are all listed as FDA approved ingredients (173.310). The product has been formulated in accordance with UNI 7550 (Requirements of water for steam generators).

SPECIFICATIONS:

Form Liquid
 Colour Colourless
 Odour..... Odourless
 Density (20 ° C) 1,3 g/cm³
 Miscibility in water Soluble
 pH (sol 1,0%) ±13,0

All information in this document is based on our practical experience and/or laboratory tests. Due to the multiplicity of conditions for usage and variable human factors, we recommend that you always test our products for suitability prior to use. At any time, this version of the product specification report may have been revised based on legislation, availability of the individual ingredients or newly acquired information. The current approved version is available upon request.

IT

Zep Italia s.r.l.

T • 800 016 918

Numero Verde Tecnico

800-579185

tecnico@zepeurope.com

www.zep.it

UK

Zep UK Ltd.

T • 0151 422 1000

F • 0151 422 1011

info@zep.co.uk

www.zep.co.uk

BE

Zep Industries BV

T • 02 347 01 17

F • 02 347 13 95

sales@zep.be

www.zepindustries.be

NL

Zep Industries BV

T • 0164 250100

F • 0164 266710

info@zepbenelux.com

www.zepindustries.nl

DE

Zep Industries BV

T • 0521 174158

F • 0521 5217114

sales@zepbenelux.com

www.zepindustries.de