



Superior Solutions



Caltar

Release agent for bituminous material

- Releases bitumen-containing materials from all surfaces.
- Resistant to temperatures in excess of 185°C.
- Does not change the technical properties of the asphalt.
- Does not cause painted surfaces to corrode.
- Surfactants are 90% biodegradable.
- For use on all objects. Does not leave any build-up on the object.
- CALTAR greatly reduces plant down time and maintenance costs.
- Water soluble at a very high dilution. Remains stable in a water solution.
- Improves the lubricity of bituminous materials.
- Used to protect lorry bodies, paver finishers, road compacters, bitumen sprayers, skip lorries, asphalt mixing plants – all types of equipment.

APPLICATION

Exceptionally strong, high performance, water based lubricant. Can be used on delivery vehicles, road building machinery, vehicle bodies, mixing machinery, loading buckets, hoppers, pavers, patching machines and all forms of equipment used in working with bitumen.

USE

Dilution for lorry bodies, skip Lorries, bitumen sprayers, equipment:

Good results are achieved with a solution comprised of one part CALTAR to 15-20 parts water. Using a spray gun, spray the solution evenly over the surface you want to protect.

Dilution for road compacters, paver finishers: a solution comprised of one part CALTAR to 30-40 parts water brings good results.

USED WITH

Our spray guns

CONDITIONS FOR USE

See the precautions for use listed on the packaging.

SPECIFICATIONS

Appearance: Clear colourless liquid

Density at 20°C: approximately 1.04

All the information in this document is based on our practical experience and/or laboratory tests. Due to the large differences in the usage conditions and the unpredictability of the human factor, we recommend that you always test our products before actual usage. At present, this technical data report may already have been reviewed based on definition of rules, available components or newly acquired information. Upon request, we shall send you the latest version that is the only valid version.

Version: 1258-0413