



Product Specification Report

Rev. 1.0

Chemseal seals hard surfaces, to reduce floor maintenance by protection of surfaces against wear and stains.

CHEMSEAL

Hard surface protectant

FEATURES:

Total protection	CHEMSEAL seals in one simple operation. Protects against wear and stains and eliminates the damaging effects of oil, grease, acids, alkalis, sugars, detergents and water.
Seals	Seals concrete and terrazzo. Adheres equally well to wood, steel plate (suitably primed), quarry tiles and stone.
Excellent finish	Gives a satin finish, does not discolour with age and prevents efflorescence and blooming.
Economical	CHEMSEAL covers up to 10m (approx. 110ft.) per litre depending on the porosity of the surface and can last up to 5 years under normal traffic conditions.
Easy to apply	The product is very easy to apply, with a brush or a roller.
10 attractive colours	Available in 10 attractive colours plus a clear version: Venetian red, white, black, dark grey, light grey, canary yellow, poppy red, french blue, pantone green, burgundy.

APPLICATIONS:

Can be used to protect hard surfaces such as concrete, terrazzo, wood, steel plate (suitably primed), quarry tiles and stone. Protects from the damaging effects of oil, grease, acids, alkalis, sugars, detergents and water.

SPECIFICATIONS:

FormLiquid
 ColourAvailable in 10 colours
 Odour.....Aromatic
 Flash point:21 – 55 °C
 Density at 20 °C0,95 g/cm³
 Solubility in waterInsoluble

INSTRUCTIONS FOR USE:

Ensure that the surface is clean and dry. Apply CHEMSEAL with a brush or lambswool roller. Certain surfaces need acid etching and ZEPs LIFTCON is recommended for this purpose. Easy to follow instructions are on every drum.

WARNING:

Please consult the safety data sheet for more information.

All information in this document is based on our practical experience and/or laboratory tests. Due to the multiplicity of conditions for usage and variable human factors, we recommend that you always test our products for suitability prior to use. At any time, this version of the product specification report may have been revised based on legislation, availability of the individual ingredients or newly acquired information. The current approved version is available upon request.



Zep Italia s.r.l.
 T • 800 016 918
 Numero Verde Tecnico
 800-579185
 tecnico@zep.europa.com
 www.zep.it



Zep UK Ltd.
 T • 0151 422 1000
 F • 0151 422 1011
 info@zep.co.uk
 www.zep.co.uk



Zep Industries BV
 T • 02 347 01 17
 F • 02 347 13 95
 sales@zep.be
 www.zepindustries.be



Zep Industries BV
 T • 0164 250100
 F • 0164 266710
 info@zepbenelux.com
 www.zepindustries.nl



Zep Industries BV
 T • 0521 174158
 F • 0521 5217114
 sales@zepbenelux.com
 www.zepindustries.de